



**www.pasmousa.com** 1-844-527-2766







## **Technical Specs:**

#### **GENERAL INFO**

MODEL NUMBER S230F

TYPE table top

PRODUCTION CAPACITY 30 L / H

NUMBER OF FLAVORS 3

NUMBER OF HOPPERS 2

 HOPPER CAPACITY
 9.5 L (2.5 gal)

 SPECIFICATIONS
 30.25" x 20.5" x 38"

 CARTON SIZE
 34.25" x 25" x 42.5"

370 Lbs **NET WEIGHT** 421 Lbs **GROSS WEIGHT** 1.6 L (.42 gal) CYLINDER CAPACITY stainless steel BEATER TYPE standard HOPPER MIXER POWER 3 Kw SELF-CHECK yes LOW MIXTURE SENSOR ves FREQUENCY CONVERSION yes

### **REFRIGERATION SYSTEM**

NUMBER OF COMPRESSORS 2

COMPRESSOR BRAND Aspera

COMPRESSOR CAPACITY 3753 Btu / hr x 2

COMPRESSOR GAS R404 A
GAS QUANTITY 500 g

REFRIGERATION TYPE air cool / water cool

#### **TRANSMISSION**

NUMBER OF MOTORS 2

MOTOR CAPACITY 550 W x 2

#### distributed by: www.frozensolutions.com 888-698-1711



# Features:

- Double control system: 2+1 twist flavors
- Offers all of the popular soft serve variations from low to non-fat ice creams, custards, yogurt, Italian ices and sorbet
- Serve two separate soft serve flavors, or an equal combination of both in a twist
- Redundant components use side while other side is off
- Self returning handles

#### **SILENT**

• Mute function, suitable for all types of environments

### **CONTINUOUS DISCHARGING ABILITY**

• Ensures continuous discharge even during peak hours

#### **DISPENSE SPACE**

- 3 7/8" of dispense space
- Can meet the needs of big cups or cake decorating

### **IMPORTED CORE ACCESSORIES**

- Aspera compressors and Danfoss expansion valves
- Ensures the service life of the machines

### **SPRING HANDLE**

- Automatic handle return
- Prevents ice cream overflow / reduces mess when not in use

### **INTEGRATED CYLINDER**

- Cornered ends prevent bacterial growth
- Easy to wash







## **Product List:**

SERIAL NUMBER	COOLING TYPE	VOLTAGES
S230FA1	air cool	220 v / 50 hz 1P
S230FA2	air cool	220 v / 60 hz 1P
S230FA3	air cool	380 v / 50 hz 3P
S230FW1	water cool	210 v / 50 hz 1P
S230FW2	water cool	220 v / 60 hz 1P
S230FW3	water cool	380 v / 50 hz 3P